

MANUFACTURE INFORMATION



EMERGENCY PHONE.....: 800-255-3924
PREPARATION/REVISION DATE: 03/10/99

TRADE NAME/SYNONYMS...: Background Antique
CHEMICAL NAME/SYNONYMS:
CHEMICAL FAMILY.....:
FORMULA.....:
PRODUCT CODE.....: 69-641

***** HAZARDOUS INGREDIENTS *****

DOES PRODUCT CONTAIN HAZARDOUS INGREDIENTS? (Y,N,N/A,N/I) : Y

CHEMICAL/COMMON NAME	CAS-NUMBER	%	PEL-OSHA	TLV-ACGIH
PETROLEUM DISTILLATE	64742-89-8	>1	300PPM	300PPM
MINERAL SPIRITS	64742-88-7	>1	100PPM	100PPM
PETROLEUM DISTILLATE	8052-41-3	>1	100PPM	100PPM

DOES PRODUCT CONTAIN CARCINOGENS (NTP, IARC, OR OSHA)? (Y,N,N/A,N/I): N

***** HEALTH HAZARD DATA *****

HEALTH EFFECTS (ACUTE AND CHRONIC)

HARMFUL IF INHALED, MAY AFFECT BRAIN OR NERVOUS SYSTEM, CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES NOSE, THROAT, EYE AND SKIN IRRITATION. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVER-EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. SIGNS AND SYMPTOMS OF EXPOSURE: BREATHING DIFFICULTY, LIGHT HEADEDNESS, DRYNESS OF RESPIRATORY TRACT.

PRIMARY ROUTES OF ENTRY

EYES, INHALATION, INGESTION AND SKIN
INHALATION MAY CAUSE DIZZINESS, LOSS OF BALANCE AND COORDINATION, UNCONSCIOUSNESS, RESPIRATORY FAILURE AND DEATH.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

ANY MEDICAL CONDITION, ALLERGY, SENSITIZATION WHICH MAY BECOME WORSE UPON EXPOSURE TO THE PRODUCT.

EMERGENCY FIRST AID PROCEDURES

EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. TAKE TO PHYSICIAN FOR TREATMENT.

INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING. CONSULT A PHYSICIAN.
INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY.
ON SKIN: WASH AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.
CONSULT PHYSICIAN.

SIGNS OF EXPOSURE: BREATHING DIFFICULTY, DIZZINESS, LIGHT-HEADEDNESS, DRYNESS OF RESPIRATORY TRACT.

***** CHEMICAL DATA *****

BOILING POINT(F)....	230F	SPECIFIC GRAVITY(WATER=1).....	0.95
VAPOR PRESSURE(MMHG)	3.5MM	PERCENT VOLATILE BY VOLUME(%).....	N/A
VAPOR DENSITY(AIR=1)	>1.0	EVAP RATE(BUTYL ACETATE =1)	>1.0

SOLUBILITY IN WATER.. NEGLIGIBLE

APPEARANCE AND ODOR INFORMATION

COLORED LIQUID , MILD ODOR

***** PHYSICAL HAZARD DATA *****

FLASH POINT (METHOD USED) 70F FLAMMABLE LIMITS-LEL= 0.7 UEL= 6.0

EXTINGUISHING MEDIA

WATER SPRAY, ALCOHOL FOAM, DRY CHEMICAL,FOAM, CO2, OR ANY CLASS B EXTINGUISHING AGENT.

SPECIAL FIRE FIGHTING PROCEDURES

WEAR SELF-CONTAINED BREATHING APPARATUS WHIN FIRE FIGHTING IN CONFINED SPACE.
IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

UNUSUAL FIRE AND EXPLOSION HAZARDS

IF WATER IS USED, FOG NOZZLES ARE PREFERRED. VAPORS ARE HEAVIER THAN AIR AND TRAVEL CONSIDERABLE DISTANCES TO A SOURCE OF IGNITION AND FLASHBACK. USE WATER FOG TO COOL CONTAINERS TO PREVENT RUPTURING.


***** REACTIVITY DATA *****

INCOMPATIBILITY (MATERIALS TO AVOID)

OXIDIZING MATERIALS CAN CAUSE VIGOROUS REACTION.

HAZARDOUS DECOMPOSITION PRODUCTS

COMBUSTION WILL PRODUCE FUMES, SMOKE CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE.



WILL HAZARDOUS POLYMERIZATION OCCUR
NO

CONDITIONS TO AVOID/POLYMERIZATION
N/A

IS THE PRODUCT STABLE
YES

CONDITIONS TO AVOID/STABILITY
N/A

***** SPILL AND LEAK PROCEDURES *****

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
ISOLATE, ABSORB AND VENTILATE(OPEN ALL DOORS,WINDOWS) REMOVAL OIF ALL IGNIT-
ION SOURCES, FLAMES AND HOT SURFACES. AVOID BREATHING OF VAPORS, USE RESPIRAT
ORY PROTECTIVE DEVICE.

WASTE DISPOSAL METHOD
IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REQUATIONS. BEFORE ATTEMPTING CL
EAN-UP REFER TO HAZARD CAUTION INFORMATION IN THE OTHER SECTIONS OF THIS FORM
.

***** EXPOSURE CONTROL INFORMATION *****

VENTILATION


LOCAL EXHAUST	NOT ADEQUATE	MECHANICAL (GEN)	NOT TO EXCEED TLV
SPECIAL.....	N/A	OTHER.....	N/A

RESPIRATORY PROTECTION
IF WORKPLACE EXPOSURE LIMITS OF PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH
APPROVED CARTRIDGE TYPE RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRON-
MENTAL CONTROL.

PROTECTIVE GLOVES
NEOPRENE (HAZARD B OR GREATER)

OTHER PROTECTIVE EQUIPMENT
CHEMICAL SPLASH GOGGLES IN COMLIANCE WITH OSHA REGULATIONS ARE ADVISED;
HOWEVEROSHA REGULATIONS ALSO PERMIT OTHER TYPES OF SAFETY GLASSES. CONSULT
YOUR SAFETY REPRESENTATIVE.

OTHER ENGINEERING CONTROLS



NONE

WORK PRACTICES

FOLLOW GOOD HOUSEKEEPING AND PERSONAL HYGIENE. PERSONAL CONTACT SHOULD BE AVOIDED.

HYGENIC PRACTICES

SEE ABOVE

***** SPECIAL PRECAUTIONS *****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

AVOID HIGH TEMPERATURES. DO NOT STORE NEAR HEAT, SPARKS OR FLAME. PREVENT PROLONGED OR REPEATED BREATHING OF VAPOR OR SPRAY MIST.

MAINTENANCE PRECAUTIONS

N/A

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. AVOID BREATHING OF VAPOR, FUMES OR DUST. KEEP OUT OF REACH OF CHILDREN. AVOID PROLONGED CONTACT WITH SKIN. DO NOT GET IN EYES. FOLLOW ALL LABEL DIRECTIONS.

OTHER COMMENTS