

# BAF Industries

## MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 58489  
 PART NUMBER: BAF-1744-1  
 PRODUCT NAME: FLITZ LIQUID METAL POLISH  
 CHEMICAL:

### SECTION I

MANUFACTURER: BAF INDUSTRIES	<b>HMIS RATING:</b>  <b>HEALTH:</b> 2 <b>FIRE:</b> 1 <b>REACTIVITY:</b> 0 <b>PERSONAL PROTECTION:</b> E	<b>NFPA RATING:</b>  <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: center;">2</div> <div style="text-align: center;">1</div> </div> <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: center;">HEALTH 0</div> <div style="text-align: center;">FIRE 0</div> </div> <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: center;">SPEC.HAZ.</div> <div style="text-align: center;">REACT.</div> </div>
ADDRESS: 1910 SO. YALE ST. SANTA ANA, CA 92704		
EMERGENCY TELEPHONE NUMBER: (800)424-9300		
INFORMATION TELEPHONE NUMBER: (714)540-3850		
DATE PREPARED: 12/01/05		

### SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
64742-48-8	ALIPHATIC HYDROCARBONS					N/EST	N/EST		10-30
1344-28-1	ALUMINA					10mg/m3	10mg/m3		10-30
61790-53-2	DIATOMITE*				Y	80mg/m3	80mg/m3		1-5
	*SEE SECTION IX								

### SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212° F	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	1.1291
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	MISCIBLE		
APPEARANCE AND ODOR:	LIGHT YELLOW GREEN WITH SOLVENT ODOR.		
OTHER INFORMATION:	pH = 8.12		

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/AV	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA :FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER.		
SPECIAL FIRE FIGHTING PROCEDURES:SELF-CONTAINED BREATHING APPARATUS.		
UNUSUAL FIRE FIGHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE.		

### SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : VERY STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

### SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN, EXCESSIVE INHALATION MAY CAUSE DROWSINESS OR NAUSEA..
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER, IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE.

**MSDS NUMBER: 58489**

**PRODUCT NAME: BAF-1744 -1 FLITZ LIQUID METAL POLISH**

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING, KEEP AWAY FROM FLAME.

OTHER PRECAUTIONS: NONE

### SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED.

PERSONAL PROTECTIVE EQUIPMENT: RUBBER GLOVES AND CHEMICAL SAFETY GLASSES AND NIOSH APPROVED DUST & VAPOR RESPIRATOR..

### SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: \*THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS), WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED INHALATION OF CS AS CARCINOGENIC FOR HUMANS (GROUP I). CS IS LISTED BY NTP AS A SUBSTANCE WHICH MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN. INHALATION IS CS IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE.

THIS PRODUCT MAY CONTAIN UP TO 1% CRYSTALLINE SILICA, CAS# 61790-53-2

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CLEANING LIQUID.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE

N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- |    |                        |                 |
|----|------------------------|-----------------|
| 1. | ALIPHATIC HYDROCARBONS | CAS# 64742-48-8 |
| 2. | WATER                  | CAS# 7732-18-5  |
| 3. | ALUMINA                | CAS# 1344-28-1  |
| 4. | DIATOMITE              | CAS# 61790-53-2 |
| 5. | SURFACTANT             | MIXTURE         |

.

V. O. C. CONTENT: 0 GRAM PER LITER.